



PREMIUM POLE AND ROPE FABRIC AWNING

INVENTORY

- 1 awning
- 1 vinyl storage bag
- Poles (# vary depending on size of awning)
- 1 length of rope per pole
- 1 steel stake per pole
- 1 plastic line tightener per pole

INSTRUCTIONS

1. Unpack awning and verify that all items above are included. Poles may be shipped separately.
2. Identify plastic awning bead running the width of the awning. Trim ends of plastic bead near flush with edges of awning fabric, if desired.
3. Inspect trailer's awning rail and repair or replace if damaged. Make sure sharp edges are smoothed to reduce friction and wear on plastic awning bead.
4. Prepare poles by slipping lower end of upper pole through lower pole's stamped metal height adjustment clip. After passing lower end of upper pole through stamped metal clip, slide the end into upper end of lower pole.
5. Prepare ropes by tying a small bight (fixed loop) in the end of each rope. Later, this bight will go over the tip of each installed pole.
6. Continue to prepare ropes by threading the opposite end of each rope through its plastic line tightener. Each rope threads through one hole in its plastic tightener and then threads back through the other hole. Finally, tie a knot in the end of the rope so that it cannot slip back through the holes in the plastic tightener.
7. Slide plastic awning bead through trailer's awning rail from either end. One "assist grommet" is located in awning near each end of plastic awning bead. Assist grommets may be used to help pull the awning along in the rail by temporarily inserting a rope or pole in one of the grommets. Assist grommets are not used after awning is fully installed.
8. When fully inserted and centered, extend awning fully and insert one pole tip in one grommet along the outside edge of the awning.
9. Place bight of rope over tip of pole on top of awning fabric.
10. Create several feet of slack in the rope in the area of the rope **between the two holes in the line tightener**. This is the section of rope the stake will hook.
11. When stake is hammered in to the ground, the plastic tightener will be located at least one foot higher than the stake.
12. Tighten rope by sliding the line tightener up away from the stake.
13. Repeat steps 7 through 11 for each pole.

WARRANTY

Fabric manufacturer offers a limited 5-year warranty from date of purchase. This is for fabric replacement only. Workmanship and non-fabric components are guaranteed by Vintage Trailer Supply to be free of defect at time of awning purchase.

CONTACT INFO

If you have any questions or concerns about your awning, please contact us at:

Vintage Trailer Supply
800-644-4620
info@vintagerv.com
www.vintagetrailersupply.com